

REDONDOS RECTIFICADOS h8

Redondos rectificados h8 DIN 7154

cromova



Tolerancia		Acabado superficial		
Diámetro	h8	N7	Rectificado	Ra 1,6
Largo	+5/0 mm.	N15	Serrado	Ra 25

Tol h8 en μ :

hasta 3 mm., 0 / -14 μ	3 a 6 mm., 0 / -18 μ	6 a 10 mm., 0 / -22 μ
10 a 18 mm., 0 / -27 μ	18 a 30 mm., 0 / -33 μ	30 a 50 mm., 0 / -39 μ

LARGO 1000 mm.
RECTIFICADO

\emptyset h8→	4	5	6	7	8	9	10	11	12	13	14	15
1.2510	●	●	●	●	●	●	●	●	●	●	●	●
1.2379			●		●		●		●			●
1.2767							●		●			●
1.2343							●		●			●
1.2210	●	●	●	●	●	●	●	●	●	●	●	●
1.3343							●		●			●
1.3247							●		●			●
1.4112	●	●	●	●	●	●	●	●	●	●	●	●

\emptyset h8→	16	17	18	19	20	22	23	24	25	30	35	40
1.2510	●	●	●	●	●	●	●	●	●	●	●	●
1.2379					●				●	●		●
1.2767					●				●	●		●
1.2343					●				●	●		●
1.2210	●	●	●	●	●	●	●	●	●	●	●	●
1.3343					●				●	●		●
1.3247					●				●	●		●
1.4112	●	●	●	●	●	●	●	●	●	●	●	●

